REQUEST FOR QUOTATION CITY OF PORT HURON

100 McMorran Boulevard Room 217

Port Huron Michigan 48060

Phone: (810) 984-9728 Fax: (810) 982-7872

DATE: 3/21/2017

| BID OPENING | | | | |
|----------------|-----------|--|--|--|
| DATE | TIME | | | |
| April 13, 2017 | 3:00 p.m. | | | |

Quotations are requested for furnishing the items described below, in accordance with the terms set forth herein. All quotations must be F.O.B. destination and include cost of boxing and cartage to delivery point below. In submitting your bid, remember that the City of Port Huron is EXEMPT FROM ALL FEDERAL AND STATES TAXES.

| QUANTITY/UNIT | DESCRIPTION | LIST | DISCOUNT | TOTAL NET |
|-----------------|--|------------------------------------|----------|-----------|
| 1 1 | Replace carpet with (please see attached specifications) Optional Add on: Cushion (please see attached specifications) | LSUM | | |
| 1 | Removal of carpet including rips up and disposal of double stick carpet | LSUM | | |
| | Include all transitions | | | |
| | As per the attached specifications and drawings. Please submit a price for each. The City reserves the right to split this bid up and do removal by in house staff. Bidder responsible for own field measurements and building will be available Monday –Friday 8am – 12pm (please report to the box office) | | | |
| | | TOTAL I | BID | |
| DELIVERY REQUES | TED DELIVERY POINT | PURCHASING AGENT ROBERTA J. SEPPO | | |

CONDITIONS

- 1. ALL QUOTATIONS MUST BE SIGNED. Enclose in an envelope plainly marked "BID".
- In submitting the above, the vendor agrees that acceptance of any or all quotations by the purchasing office within a reasonable period constitutes a contract.
- 3. Right is reserved to reject any or all bids, or to accept separate items in a bid, unless the right is denied by bidder.
- In case of default, the municipality may procure its supplies from other sources, and hold the original bidder or contractor liable for resulting increased costs.
- Samples, if requested, must be furnished at bidders expense and, if not destroyed in testing, or retained as a standard, will be returned on same terms, if requested.
- 6. The purchasing Agent reserves the right to increase or decrease by ten per cent the quantities of any item or items ordered.

NOTICE: QUOTATIONS ON ANY FORM OTHER THAN THIS WILL NOT BE CONSIDERED.

COMPANY NAME: AUTHORIZED SIGNATURE: TITLE: DATE:

both flights up to 2nd flaar

McMorran

Entire job

Customer Name:
Customer Address:
Customer Address:
Customer Address:
Job Info:
Telephone #1:
Telephone #2:
File Name:

Inetworkshare\Share\Candy\My Documents\FloorRight\McMorran 17 lobby isles stairs up.flr

Tue Mar 21 15:13:34 2017

| | | | V- |
|-----|--|--|---|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | 189 |
| | | | 111111111111111111111111111111111111111 |
| | | | |
| | | | |
| | | | 74177 |
| | | | II AS II |
| | | | |
| | | | |
| | | | |
| | | | OLA TO TOTAL |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | 72 |
| | | | |
| | | | AN |
| | | | |
| | | | |
| | | | M. |
| | | | 1 |
| | | | |
| e d | | | |



FH73P COLORSHIELD PLUS 36

PILE YARN CONTENT FABRIC TYPE GAUGE

 GAUGE
 1/10

 STITCHES PER INCH
 13.3

 AVERAGE PILE THICKNESS
 .160

 TUFTED FACE WEIGHT
 36.00

 DENSITY
 8,100

 WEIGHT DENSITY
 291,600

DYE METHOD Precision Dye Injection

BACKING Weldle

PERFORMANCE FLAMMABILITY:

PILL TEST 16GFR-1630.4 (FF-1-70) FLOORING RADIANT PANEL ASTM E-648

SMOKE DENSITY ASTM E-662 COLORFASTNESS:

LIGHTFASTNESS AATCC 16E CROCKING AATCC 165 ATMOSPHERIC CONTAMINANTS AATCC 129,

STATIC:

STATIC PROPENSITY AATGC 134 (STEP)

PERFORMANCE CERTIFICATION:

IAQ CERTIFICATION
GREEN LABEL PLUS
CRI ARREADANCE PATIN

CRI APPEARANCE RATING GUIDELINE

Weldlok®

Textured Patterned Cut

Fortis Nylon with ColorShield/Sentry Plus

Meets or exceeds Requirement Class 1 450 or Less

Min. Rating 4 @ 60 AFU Min. Rating 4 Wet or Dry

Min. Rating 3 @ Two Cycles

Less than 3.5 K.V.

14866678 6678 Severe

III Mohawk Group

160 South Industrial Blvd. - Calhoun, GA 30701 - 800.241.4580
Mohawk Industries | Legal | Copyright © 2017 Mohawk Industries, All rights reserved

72×72 Pattern Repeat PROduct # D46916



Weldlok AIR

Broadloom Backing with Integrated Cushion

Primary Backing

Thermoset Adhesive

Reinforced Woven Synthetic

Post Consumer Recycled PET Cushion

The next evolution in attached cushion backed broadloom, Weldlok® AIR offers substantial sound reduction and enhanced comfort under foot. It also incorporates up to 50% recycled content (pre-and post-consumer) by total product weight.



PERFORMANCE

- · For use with direct glue installations
- Standard backing with attached cushion designed for commercial applications
- Increased load deflection reduces physical stress and provides comfort under footthe perfect solution for today's sit/stand work environments
- Noise Reduction Coefficient = 0.3, reduces ambient sound by 30%
- Impact Insulation Class 70.
 Performs more than 2x better in reducing sound transmission than hard surfaces and 40% better than standard carpet
- Provides additional thermal resistance (R-Value)
- Reduces the risk of injuries in the event of a slip or fall-a common concern in Healthcare and Assisted Living facilities



SUSTAINABILITY

- · Recyclable
- · Contains no plasticisers
- PET cushion layer of Weldlok® AIR contains 65% post-consumer recycle
- Finished product contains a total of 38% pre-consumer and 12% post-consumer recycle content; total 50% recycle content by finished product weight.
- May contribute or comply with LEED credits MR 4.0, MR 5.0, IEQ 4.3 and innovation credit of NSF 140
- Certified NSF/ANSI 140 PLATINUM with a minimum of 14% post-consumer recycle content
- Certified low VOC's under CRI Green Label Plus Program
- Compliant with LEED EQ 4.1 low VOC emitting when installed with Durkan adhesive and seam sealer



BUDGET

 Standard backing with attached cushion for budget conscious projects



SERVICE

 Contact your sales representative for more information







INSTALLATION SPECIFICATIONS

| Backing | Adhesive | Adhesive Application Method | Moisture & pH | Spread Rate | Seam Sealer |
|--------------|--|---|----------------------|--------------|--|
| Weldlak* Air | Mohawk NuBroadlok Premium Multi-Purpose | Direct Glue: 1/8" x 1/8" x 1/8" U Notch Trowel Direct Glue: 1/8" x 1/8" x 1/16" V Notch Trowel | 5lbs/ 80% RH, 5-9 pH | 8- 10 SY/Gal | Mohawk NuBroadlok Latex Seam Sealer |

CUSHION SPECIFICATIONS

| Padding | Thickness | Weight | Density | Cushion |
|--------------|---|-----------|------------|---|
| Weldlok" Air | Cushion thickness .165" + Carpet Finish Pile thickness - Total Pile thickness | 17 oz./SY | 8 lbs./FT3 | Non-woven needle punch post-consumer PET |

^{*} Mohawk Optiseal™ required for installations with subfloor moisture exceeding 5 lbs and/or 80% RH. Maximum allowable moisture with Optiseal™is 90% RH.

10 YEAR LIMITED WARRANTY*

10 YEAR LIMITED TUFT BIND Maintains superior tuft bind performance

10 YEAR LIMITED DELAMINATION Carpet will not delaminate (separate from backing)

10 YEAR LIMITED CUSHION RESILIENCY Maintains cushion properties

^{*} See Mohawk Group official warranty documents for further details at www.mohawkgroup.com LEED®and the related logo is a trademark owned by the U.S. Green Building Council and is used with permission.

| | | | And the second s |
|--|--|--|--|
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |